

बिहार राज्य भवन निर्माण निगम, लि० पटना
 (बिहार सरकार का उपक्रम)
दर आमंत्रण हेतु कोटेशन आमंत्रण सूचना सं०-67/2018-19

भवन निर्माण विभाग के निबंधित संवेदकों/ख्याति प्राप्त फर्मों/कंपनियों से दिनांक: 10.09.2018 के अपराह्न 3:00 बजे तक निम्नलिखित कार्यों के लिए मुहरबंद कोटेशन उप महाप्रबंधक, पी०आई०यू०, पटना/महाप्रबंधक (उत्तर/दक्षिण)/मुख्य महाप्रबंधक, बिहार राज्य भवन निर्माण निगम लि०, पटना के कार्यालय में प्राप्त किया जाएगा और उसी दिन 3:30 बजे अपराह्न में कोटेशनदाताओं या उनके द्वारा अधिकृत प्रतिनिधियों के समक्ष खोला जायेगा।

कार्य का विवरण:-

क्रम सं०	योजनाकानाम	कार्य की विवरणी	ईकाई	उद्धृत दर
1	2	3	4	5
1		110 mm OD UPVC SWR pipe.For 3mtrs length of single socket solvent joint pipe.	each	
		PVC SWR plain bend .110 mm dia	each	
		UPVC SWR single equal Access Door Tee 110 x 110 x 110 mm	each	
		UPVC SWR single equal plain 'Y' junction 110 x 110 x 110 mm	each	
		UPVC SWR double equal plain 'Y' junction 110 x 110 x 110 x 110 mm	each	
		UPVC Cowl junction 110 mm OD	each	
		UPVC SWR P or S trap (Floor Trap)	each	
		UPVC multi angle inlet hight riser fittings with 3 or 4 side inlets of 40, 50 & 63 mm size	each	
		UPVC clean out plug with suitable insert keys for opening in PVC cap, male threaded 110 mm	each	
		floor drain of 110x63 mm OD	each	
11		UPVC pipes conforming to IS 4985 class III (6 kg/cm ²) including injection moulded fittings with bosses like bends, tees, adaptors etc. suitable for rubber ring		
a		40 mm dia (Cost for 10 mtr pipe)	each	
b	विभिन्न जिलान्तर्गत 720	50 mm dia (Cost for 10 mtr pipe)	each	
c	क्षमता वाले अनुसूचित	63 mm dia (Cost for 10 mtr pipe)	each	
d	जनजाति आवासीय	75 mm dia (Cost for 10 mtr pipe)	each	
e	विद्यालय के निर्माण में	110 mm dia (Cost for 10 mtr pipe)	each	
12	पी०एच०ई० से संबंधित कार्य।	Chlorinated Polyvinyl Chloride (CPVC) pipes having thermal stability for hot and cold water supply including all CPVC plain & brass threaded fittings		
		40 mm dia SDR-11 (Cost for 10 mtr pipe)	each	
13		thermal insulation tubing for hot water pipes (exposed/chases/burried locations), over pipes of following nominal bores and thickness including all required accessories, protection		
a		15mm dia (6 mm thick insulation)	each	
b		20mm dia (6 mm thick insulation)	each	
c		15mm dia (9 mm thick insulation)	each	
d		20 mm dia (9 mm thick insulation)	each	
e		25 mm dia (9 mm thick insulation)	each	
f		32 mm dia (9 mm thick insulation)	each	
g		15 mm dia (13 mm thick insulation)	each	
h		20 mm dia (13 mm thick insulation)	each	
i		25 mm dia (13 mm thick insulation)	each	
j		32 mm dia (13 mm thick insulation)	each	
k		40 mm dia (13 mm thick insulation)	each	
l		50 mm dia (13 mm thick insulation)	each	
14		Cost of Material 40 mm dia Nitrile rubber insulation 9 mm thick	each	

